(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 13 January 2005 (13.01.2005)

PCT

(10) International Publication Number WO 2005/003674 A1

(51) International Patent Classification7:

F41A 13/08

(21) International Application Number:

PCT/IB2004/051060

(22) International Filing Date: 30 June 2004 (30.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003/5148

2 July 2003 (02.07.2003) ZA

(71) Applicant (for all designated States except US): DENEL (PTY) LTD [ZA/ZA]; 368 Selbourne Avenue. Centurion. 0182 Pretoria (ZA).

(72) Inventor; and

(75) Inventor/Applicant (for US only): PAUL, Lothar Alwin [ZA/ZA]; 45 Janet Street, Eldoraigne, 0157 Pretoria (ZA).

(74) Agent: D M KISCH INC: P O Box 781218, 2146 SAND-TON (ZA). (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW. GH. GM. KE. LS. MW, MZ. NA. SD. SL. SZ. TZ. UG. ZM. ZW). Eurasian (AM. AZ. BY. KG, KZ. MD. RU. TJ. TM). European (AT. BE, BG. CH. CY. CZ. DE. DK. EE. ES. FI. FR. GB. GR. HU. IE. IT. LU. MC. NL. PL. PT. RO. SE. SI. SK. TR), OAPI (BF, BJ. CF. CG. CI. CM. GA. GN, GQ. GW. ML. MR. NE, SN, TD. TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FUME EXTRACTOR



(57) Abstract: This invention relates to a fume extractor (10) for extracting fumes from a bore (12) of a barrel (14) of a gun and comprising an annular main reservoir (16); an annular inlet reservoir (18); and an annular auxiliary reservoir (20), all concentrically surrounding the barrel (14) and being in communication with each other and the bore (12). The inlet reservoir (18) is sandwiched between the main reservoir (16) and the barrel (14). The auxiliary reservoir (20) is sandwiched between the main reservoir (16) and the barrel (14) and is located adjacent the inlet reservoir (18) on a muzzle brake end thereof. The arrangement is such that the main reservoir (16) is pressurised when the gun is fired and such that the fumes in the bore (12) are extracted by the release of pressure in the main and auxiliary reservoirs (16) and (20), after the projectile has left the barrel (14). The communication between the inlet reservoir (18) and main reservoir (16) consists of plurality of ports (24) distributed circumferentially each port being provided with a check valve (30).